Instructions for wear The equipment must be checked for Proof of correct operation and safety, especially maintenance checks of play equipment the points listed below: Wooden parts Playground 1. Check for rot and, if necessary, smooth out Date of installation splinters and round off sharp edges of cracks. Checks depend on the type of equipment. Check that all bolts and screws are tight and Any equipment with moving parts must retighten if necessary. be checked at least twice a year, static equipment at least once a year. Recommendation: apply paraffin wax to the upper end grain areas once a year, please Intervals for maintenance work and checks generally depend on refer to Order No. 0.90100, 1 litre. 4. Check the ash wood rungs of the ladder for - location wear and tear, the remaining diameter must - kind of use be at least 30 mm. - frequency of use - possible vandalism **Inclined Climbing Net** For more details see also "General 5. Check that connection points are tight and instructions for maintenance of retighten if necessary. playgrounds". Check the climbing net for wear and tear, if the steel reinforcement is damaged it is **Platform House** imperative it be replaced. Order No. 4.14904 Slide Check the slide surface for vandalism. Check that all screws and bolts are tight, retighten if necessary. Structural stability In order to check for rot at wooden parts Special notes, e.g. for repairs or steel feet for corrosion, uncover the foundations once a year. 10. Net: check the connection (tensioning hook) to the anchoring chain, if necessary retension the net at the bottom ends. Repair not carried out, it is still possible to play on equipment Repair not carried out, equipment is taken out of action All work carried out, everything is in order Maintenance carried out by: Date