Instructions for wear checks of play equipment		The equipment must be checked for correct operation and safety, especially the points listed below:		Proof of maintenance	
Playground		Bearing (axle)			
Date of installation	1.	Check the rotary motion for smoothness (it must be possible to turn the gripping plate with one hand)			
Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	2.	Lubricate once a year (Lubricating nipple is located inside the housing on the floor)			
Intervals for maintenance work and checks generally depend on	3.	Remove the top cover of the housing and grease the gearwheels (see detail).			
- location		Braking mechanism			
 kind of use frequency of use possible vandalism For more details see also "General instructions for maintenance of playgrounds".	4.	Check the braking disc for cleanliness, if necessary remove the rubber and clean (remove the bottom cover of the housing and the small floor plate between the housing and the railing), the safety bar must be in position for "free wheeling".			
Big Wheelchair Carousel Order No. 6.29000	5.	Check the setting of the brake, brake must engage at 8 cm.			
	6.	Adjusting of the brake mechanism: Put the safety bar in the upright position, shift the setting collar and adjust.			
		Structural stability			
	7.	Check the fasting of the carousel to the foundation frame once a year; tighten the screws if necessary.			
				Special notes, e.g. for repairs	
Detail				Speci	
		pair not carried out, s still possible to play on equipment			
		Repair not carried out, equipment is taken out of action			
		work carried out, erything is in order			
Maintenance carried out by:					