Instructions for wear checks of play equipment

Playground

Date of installation


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- location
- kind of use
- frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".

Climbing Structure 06 Order No. 6.51006/L6.51006



ar ipment	co	The equipment must be checked for correct operation and safety, especially the points listed below:		Proof of maintenance	
		Wooden parts			
	1.	Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks.			
uipment. s must static	2.	Check that all bolts/screws and all wood connections are tight and retighten if necessary.			
nd checks	3.	Recommendation : apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre.			
		Ropes, chains and rope nets			
	4.	Check for wear and tear, if worn heavily, it is imperative they be replaced.			
ieral f	5.	Check connections and swages.			
		Structural stability			
	6.	In order to check for rot at wooden parts or steel feet for corrosion, uncover the foundations once a year.			
)6					
				Special notes, e.g. for repairs	
				Special notes	
	Repair not carried out, it is still possible to play on equipment				
	Repair not carried out, equipment is taken out of action				
		work carried out, erything is in order			
	Maintenance carried out by:				
		Date			