Instructions for wear checks of play equipment	The equipment must be encored for		Proof of maintenance	
Playground Date of installation Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year. Intervals for maintenance work and checks generally depend on	In order to check for rot at wooden parts steel feet for corrosion, uncover the fountions once a year. Single equipment Please pay attention to the separate maintenance notes of the following single equipment:	nda-		
 location usage frequency of use possible vandalism For more details see also our general instructions for maintenance of playgrounds!	Square Tower, h=2.00m with ladder Climbing Rope with beam 3 Stainless Steel Slide 3 Support Frame 5 for Suspension Bridge for Tower Support Frame 3	der No. 3.20600 3.69453 3.63420 3.66065		
Tower Combination 60 Order No. L2.60000	for Suspension Bridge Platform, h=2.00m Inclined Climbing Net for Platform Bent Fireman's Pole 3	3.66110 3.26500 3.69180 3.69464 3.67499 s are		Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipmer Repair not carried out, equipment is taken out of action All work carried out, everything is in order	nt		
For spare parts refer to back of page.	Maintenance carried out by:	Date		

Spare parts
Tower Combination 60
Order No. L2.60000



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

Sidel No. L2.80000			
Order No.	Spare parts	Order No.	Spare parts
0.92620	Ladder for tower with roof 6 rungs	99.00240 99.00250	Roof spruce, impregnated Roof larch
0.98310	Single rung		
0.30050	Tower cladding, length 3.25 m spruce, impregnated		
0.30060	Tower cladding, lenght 3.25 m larch		