Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Wooden parts	
Date of installation	1. Check for rot and, if necessary, smooth out splinters and round off sharp edges of	
Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.	cracks.2. Check that all bolts and screws are tight and retighten if necessary.	
Intervals for maintenance work and checks generally depend on	 Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm. 	
 location usage frequency of use 	4. Recommendation : apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre.	
- possible vandalism	Structural stability	
For more details see also our general instructions for maintenance of playgrounds!	 In order to check for rot at wooden parts and steel feet for corrosion, uncover the foundations once a year. 	
Transparent Square Tower with ladder without roof Order No. L3.20530 height 1.50 m Order No. L3.20631 height 2.00 m		Special notes, e.g. for repairs
	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
For spare parts	Maintenance carried out by:	
refer to back of page.	Date	

Page 2

Order No. Spare parts	
0.92630 Ladder	
0.98310 Single rung	
0.30053 Tower cladding, length 2.80 m spruce, impregnated	
0.30063 Tower cladding, length 2.80 m larch I I II IIIIIIIIIIIIIIIIIIIIIIIIIIIIII	
Please indicate length and width!	