This copy may be copied for maintenance of Richter play equipment.				
Instructions for wear checks of play equipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance		
Playground  Date of installation	Wooden parts     Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks.     Check that all bolts and screws are tight and retighten if necessary.     Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm.     Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre.  Structural stability     In order to check for rot at wooden parts and steel feet for corrosion, uncover the			
Pentagonal Tower with ladder and roof Order No. L3.20750 height 1.50 m Order No. L3.20800 height 2.00 m	foundations once a year.	Special notes, e.g. for repairs		
	Repair not carried out, it is still possible to play on equipment			
	Repair not carried out, equipment is taken out of action			
	All work carried out, everything is in order			
For spare parts refer to back of page.	Maintenance carried out by:Date			

Spare part Pentagonal Order No. L	ts Tower 3.20750/L3.20800	Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to <b>only use original parts</b> .
Order No.	Spare parts	
0.92620	Ladder	
0.98310	Single rung	