| Instructions for wear checks of play equipment | The equipment must be checked for correct operation and safety, especially the points listed below: | Proof of maintenance | |
|---|---|---------------------------------|--|
| Playground | Structural stability | | |
| Date of installation | In order to check steel feet for corrosion, unco- ver the foundations once a year. | | |
| Checks depend on the type of equipment. Any equipment with moving parts must | | | |
| be checked at least twice a year, static | Single equipment | | |
| equipment at least once a year. Intervals for maintenance work and checks | Please pay attention to the separate maintenance notes of the following single equipment: | | |
| generally depend on | Order No. Platform, height 1.50 m L3.26300 / K3.26300 | | |
| - location - usage | Ladder attachment to long side 3.67370 | | |
| frequency of use possible vandalism | Ladder attachment to short side 3.67360 | | |
| For more details see also our general | Bottom sand chute 5.97060 | | |
| instructions for maintenance of playgrounds! | Curved sand chute 5.97090 | | |
| playgrounds | Inclined Climbing Net 3.69160 | | |
| Building Site 02 Order No. L5.02000 / K5.02000 | Sand Tray 5.97070 | | |
| | Sand Wheel 5.97130 | | |
| | Sand Hoist with Shovel 5.97000 | | |
| | Note: Please check that all documents are included! | Special notes, e.g. for repairs | |
| | Repair not carried out, it is still possible to play on equipment | | |
| | Repair not carried out, equipment is taken out of action | | |
| | All work carried out, everything is in order | | |
| | Maintenance carried out by: | | |
| | Date | | |

Page 2

Spare parts Building Site 02 Order No. L5.02000 / K5.02000



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts.**

| Order No. | Spare parts | Order No. | Spare parts |
|-----------|--|-----------|---------------------------------------|
| 0.97000 | Sand Hoist, complete | 0.97090 | Bent Sand Pipe |
| | | | Ð |
| | | | |
| 0.07040 | Trans accuration in the | 0.97070 | Sand Chute |
| 0.97010 | Turn round roll with protection block | | 1 Ray |
| | | | |
| 0.97160 | Protection Block without | 99.00420 | Block for Sand Chute |
| 0.57 100 | Turn Round Roll | 33.00420 | |
| | | | |
| | | 99.00320 | Upper Part for Sand Chute |
| 0.97020 | Replacement Chain, complete | | |
| | \int | | |
| | ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | 99.00330 | Lower Part for Sand Chute |
| 0.97030 | Tyre Segment | | |
| | | | |
| 0.97032 | Tyre Segment complete with Chain | 0.97130 | Sand Wheel |
| | Λ | | |
| | 1A | 0.97082 | Ladder, 5 rungs |
| 0.07440 | | 0.07002 | |
| 0.97140 | Tyre Segment without Chains | | |
| | | 0.98300 | Single rung |
| 0.97050 | Shovel with Chain | | |
| | | | |
| 0.97060 | Lower Sand Pipe | 0.30100 | Timber for Handrail for Short Side |
| | | | |
| | | | |
| | | 0.30110 | Timber for Handrail for Long Side |
| 0.97100 | Mounting Plate, top, incl. bolts | | |
| | t₁ ¹ t ♥ :: | 0.97105 | Plate f. Refurnishment of Stand Posts |
| 0.97110 | Mounting Plate, bottom | 0.37103 | |
| | incl. bolts | | |
| | ¢ | | |